

Recessed Lighting

4" Slim LED Downlights

AFR4-0930-WH (White)

AFR4-0930-BK (Black)

AFR4-0930-BN (Brushed Nickel)

Project _____

Date _____

Type _____

Location _____

Comments _____

Product Specifications

| | |
|-----------------|------------------------------------|
| Description: | 4" Slim LED Downlights |
| Wattage: | 9 |
| Dimensions: | 5" Overall Diameter 1/2" Height |
| Cut Out | 4 1/8" – 4 1/4" |
| Lens: | Frosted |
| Finish: | White Black Brushed Nickel |
| Input Voltage: | 120V |
| Output Voltage: | 20-25V DC |
| Life: | 36,000 hours |
| Initial Lumens: | 570 |
| Colour Temp: | 3000K (warm white) |
| CRI: | > 80 |
| Beam Angle: | 110° |
| Dimmable: | Yes (with compatible dimmer) |
| Power Factor: | > 0.90 |
| Equivalent: | 50W Halogen |
| Operating Temp: | -40°C ~ 40°C |
| Listing: | Suitable for wet locations |
| Type IC: | Suitable for insulated ceilings |
| Certifications: | cETLus / Energy Star |



Includes one junction box with quick connectors and factory-installed driver inside.



| DIMMER COMPATIBILITY LIST | | |
|---------------------------|---------------|--------------|
| BRAND | MODEL | DIMMING RATE |
| LUTRON | CTCL-153PDH | 100-20% |
| | CTCL-153P | 100-20% |
| | CT-600P | 100-20% |
| | DVCL-153P | 100-20% |
| LEVITON | 6672 | 100-20% |
| | 6674 | 100-20% |
| PASS & SEYMOUR | HCL453PTCCCV6 | 100-20% |



Distributed By

