

4" Slim LED Downlight

Part Number

R4-D30ES-BK

Project _____


Date _____

Type _____

Location _____

Product Specifications

Description	4" Round Slim Recessed LED
Finish	Black
Wattage	9W = 50W Halogen
Dimensions	5" Outer Diameter x 1/2" Height
Cut Out	Ø 4-1/8" – 4-1/4"
Dim Capacity	Dimmable (with compatible TRIAC dimmer) Dimmable down to 10%
Rated Lamp Life	Up to 50,000 hours
Brightness	600 Lumens
Colour Temp.	3000 Kelvins (warm white)
Colour Rendering	≥ 80 CRI
Operating Temp.	-40°C to 40°C (-40°F to 104°F)
Beam Angle	110° beam
Certifications	cETLus Energy Star Certified Certified to CSA standards Suitable for wet locations Type IC rated for direct contact with insulation
Features	120V 60Hz Slim 1/2" design fits in limited ceiling space Reduce labour time with quick installation No potlight housing required 5 year limited warranty



Includes one junction box with quick connectors and factory-installed driver inside.



4" Slim LED Downlight

Part Number

R4-D30ES-BK

120V Compatible Dimmers	
BRAND	MODEL
LUTRON	CTCL-153PDH
	CTCL-153P
	CT-600P
	DVCL-153P
LEVITON	6672
	6674
PASS & SEYMOUR	HCL453PTCCCV6

