

3" LED Round Gimbal Downlight

Product Code

AFR3G-0730-BN

Finish

Brushed Nickel

Project _____

Date _____

Type _____

Location _____

Product Specifications

Energy Used	7.5W = 50W Halogen
Dimensions	3-3/8" Outer Diameter x 1-3/4" Height
Cut Out	2-3/4"
Input Voltage	AC 120V 60Hz
Output Voltage	DC 36V, CC 170mA
Lamp Life	36,000 hours
Initial Lumens	600 lm
Colour Temperature	3000K (warm white)
Colour Rendering	> 80 CRI
Beam Angle	44°
Power Factor	> 0.9
Dim Capacity	Dimmable (with compatible dimmer)
Operating Temp.	-40°C ~ 40°C
Warranty	Limited 5 year (conditions may apply)
Approved Location	For insulated ceilings (IC) Suitable for damp locations
Listed	cETLus

Features


- Slim 1-3/4" design fits where ceiling space is limited
- Reduce labour time with fast and easy installation
- No housing or junction box required



Adjustable Gimbal



Includes integral driver
in connection box.
(No junction box required)



3" LED Round Gimbal Downlight

Product Code

AFR3G-0730-BN

DIMMER COMPATIBILITY LIST		
BRAND	MODEL	DIMMING RATE
LUTRON	CTCL-153PDH	100-20%
	CTCL-153P	100-20%
	CT-600P	100-20%
	DVCL-153P	100-20%
LEVITON	6672	100-20%
	6674	100-20%
PASS & SEYMOUR	HCL453PTCCCV6	100-20%

