

4" Gimbal LED Downlight

Part Number

R4G-D30ES-BN

Project _____

Date _____

Type _____


Location _____

Product Specifications

Description	4" Round Gimbal Recessed LED
Wattage	12W = 90W Halogen (energy saving)
Dimensions	Ø 5" Outer Diameter x 2" Height Ø 3-1/8" Gimbal Diameter
Cut Out	Ø 4-3/16"
Finish	Brushed Nickel
Dim Capacity	Dimmable (with compatible TRIAC dimmer)
Rated Lamp Life	Up to 50,000 hours
Brightness	833 Lumens
Colour Temp.	3000 Kelvins (warm white)
Colour Rendering	≥ 90 CRI
Operating Temp.	-40°C to + 40°C (-40°F to 104°F)
Beam Angle	40° beam with 30° tilt & 360° rotation
Certifications	cETLus Certified to CSA standards Suitable for wet locations (Air-tight)
Features	120V 60Hz Slim 2" design fits in limited ceiling space Type IC rated Approved for direct contact with insulation Reduce labour time with quick installation No housing or junction box required Ideal for soffit installation and accent lighting



Includes one junction box with quick connectors and factory-installed driver



4" Gimbal LED Downlight

Part Number

R4G-D30ES-BN

120V Compatible Dimmers	
BRAND	MODEL
LUTRON	TGCL-153PH
	LGCL-153PH
	MACL-153M
	DVCL-153P
	CTCL-153P
LEVITON	6672
	6674
	IPL06
PASS & SEYMOUR	HCL453P
Cooper	SAL06P

