

# 4" Gimbal LED Downlight

Part Number

**R4GD-D30ES-BN**

Project \_\_\_\_\_

Date \_\_\_\_\_

Type \_\_\_\_\_


Location \_\_\_\_\_

## Product Specifications

|                  |  |
|------------------|--|
| Description      | 4" Round Gimbal Recessed LED   |
| Finish           | Brushed Nickel   |
| Wattage          | 9W = 60W Halogen   |
| Dimensions       | Ø 5" Outer Diameter x 1-1/2" Height<br>Ø 3-1/8" Gimbal Diameter  |
| Cut Out          | Ø 4-1/8"   |
| Dim Capacity     | Dimmable (with compatible TRIAC dimmer)<br>Dimmable down to 10%  |
| Rated Lamp Life  | Up to 35,000 hours   |
| Brightness       | 700 Lumens   |
| Colour Temp.     | 3000 Kelvins (warm white)  |
| Colour Rendering | ≥ 80 CRI   |
| Operating Temp.  | -40°C to + 40°C (-40°F to 104°F)   |
| Beam Angle       | 40° beam angle (30° tilt angle)  |
| Certifications   | cETLus   Certified to CSA standards<br>Suitable for damp locations<br>Type IC rated for direct contact with insulation   |
| Features         | 120V   60Hz<br>Slim 1-1/2" design fits in limited ceiling space<br>Reduce labour time with quick installation<br>No potlight housing required<br>Ideal for soffit installation and accent lighting |



Includes one junction box with quick connectors and factory-installed driver



# 4" Gimbal LED Downlight



| 120V Compatible Dimmers |            |
|-------------------------|------------|
| BRAND                   | MODEL      |
| LUTRON                  | TGCL-153PH |
|                         | LGCL-153PH |
|                         | MACL-153M  |
|                         | DVCL-153P  |
| LEVITON                 | 6672       |
|                         | 6674       |
|                         | IPL06      |
| PASS & SEYMOUR          | HCL453P    |
| Cooper                  | SAL06P     |

